BUILDING SURVEY INSPECTION KIT



The Tramex Building Survey Inspector Kit is a complete moisture and humidity testing kit featuring the multifunctional Moisture Encounter MEX5 digital moisture meter allowing for non-invasive testing of moisture conditions in numerous building materials such as drywall, wood, plaster, brick, ceramic tiles, resilient flooring, laminates and roofing. The MEX5 has a built-in hygrometer and infrared surface thermometer for testing ambient relative humidity, temperature and dew point, and surface temperature. These can be used to identify detrimental condensation conditions conducive to microbial mold growth can also be identified. The heavy-duty handheld pin-probe and hammer-action pin-probe measure moisture content in wood, and the insulated 200mm (7.8") pins and narrow 260mm (10") RH probe allow for in-situ probing. The Tramex Building Survey Inspection Kit comes with an extension handle and a protective heavy-duty carrying case with die-cut foam lining.



KIT CONTENTS

- 1. Moisture Encounter MEX5
- 2. App available for Android and iOS (phone not included)
- 3. Heavy-duty pin-type wood probe
- 4. Hammer-action wood probe

- Product Code: BSIK
- 5.7.8" (200mm) insulated pins for in-depth penetration
- 6.10" (260mm) Narrow Wand Relative Humidity Probe
- 7. Calibration Check Salts
- 8. Extension handle



1)	
	 ┉┯┙	
	/	

WTRAMEX
AMBIENT RH, T, DP, g/kg

0-30%
WOOD %MC

	~
6-5	0%
woon %	MC PIN





kJ/kg	



NON-DESTRUCTIVE

DUAL DEPTH

READING RANGE

READING RANGE

DRYWALL %MC PIN READING RANGE

SURFACE TEMPERATURE

ENTHALPY



SPECIFICATIONS

MOISTURE ENCOUNTER MEX5



The Tramex Moisture Encounter MEX5 is a digital Dual-Depth, non-destructive moisture meter for wood and various building materials such as drywall, roofing, plaster, tile and masonry. The Moisture Encounter MEX5 has a built-in hygrometer for ambient conditions and psychrometric values, an Infrared Surface Thermometer and also incorporates external in-situ RH probes for in-situ equilibrium RH readings, as well as Pin probes for wood, drywall, and WME readings.

Moisture test results can be visualized and Geotagged with the Tramex Meters App and turned into moisture maps, reports and charts for sharing.

Size:	180mm x 85mm x 40mm (7.1" x 3.4" x 1.6")	
Weight:	290g (10.22 oz)	
Constructio	on: ABS Body	
Power:	2 x AALR6 ALKALINE (included)	
Display:	Digital 58 mm x 35 mm (2.3" x 1.4")	
Depth of penetration:		
Shallow sig	nal: up to 9mm (³⁄ଃ")	
Deep signal	up to 30mm (1½4")	

Wood Moisture Content (NDT):0 to 30% MCWood Moisture Content (Pin):6% to approx 50% MCDrywall Moisture Content (Pin):0 to 8.5% MCReference scales for building materials:0 - 100Relative Humidity:0 - 99%Humidity Accuracy: $0\% \rightarrow 99\%$ RH +/- 2% @ 25° C / 77°F

KIT SPECIFICATIONS

Size: Power: 16.5" x 14.2" x 5.5" (42cm x 36cm x 14cm) 2 x AALR6 ALKALINE (included)

Weight:

9.5lbs (4.3kg)





